

GFC
Milano - Made in Italy

Fata



*The Italian
Frame Heater*

GENERAL INFORMATION ON THE NEW *Fata* FRAME HEATER

FRAME HEATER EXTERIOR

- High quality and very resistant **aluminium extrusion body** never becomes hot, thanks to the interior **air flow**, that “refreshes” the interspace between the aluminium body and the motor and resistance holders’ cones.
- **Modern design in every single detail**, a further touch to the optical shops’ bench.
- The **plastic parts** are very high temperatures resistant.
- The hot air **concentrator** is included in each FATA pack.



FRAME HEATER INTERIOR

- The new **motor holder** and **resistance holder** are in glass fiber nylon.
- The **heating element**, studied and manufactured by GFC, permits to reach the 190°C temperature (mounting the hot air concentrator) with a consumption of 350W only.
- The heating element of the Fata frame heater is **10 years guaranteed** by GFC.
- In case of dangerous temperature, the **thermostat**, mounted on the heating element, cuts the power itself.

FRAME HEATER – PLUS VERSION

- **Cold air** is available in Plus version when the led light is green.
- The knob rotation turns the **LED** firstly to orange then to red, when the frame heater reaches the maximum temperature.

Like all the GFC equipments, this new frame heater has been studied to meet the **EEC rules** and it meets the **safety rules of the electric and electronic equipments**.

Fata

- Horizontal
- No heating regulation



Cod. A 4000 /WH

OPAQUE
WHITE

BRI
BLACK
Cod. A 4000 /BK

BRILLIANT
BLACK

Fata⁺

- Horizontal
- Heating regulation
- Cold air



Cod. A 4000P /WH

OPAQUE
WHITE

Cod. A 4000P /BK

BRILLIANT
BLACK

Fata up

- Vertical
- No heating regulation



Cod. A 4100 /WH

OPAQUE
WHITE

Cod. A 4100 /BK

BRILLIANT
BLACK

Fata up⁺

- Vertical
- Heating regulation
- Cold air



Cod. A 4100P /WH

OPAQUE
WHITE

Cod. A 4100P /BK

BRILLIANT
BLACK

TECHNICAL INFORMATION

FRAME HEATER	<i>Fata</i>	<i>Fata up</i>
Code	A4000 wh/bk - A4000P wh/bk	A4100 wh/bk - A4100P wh/bk
Maximum length	300 mm	180 mm
Maximum width	120 mm	120 mm
Maximum height	155 mm	320 mm
Machine weight	1.6 Kg	1.7 Kg
Working temperature	Till 150 °C (190°C with the hot air conc.)	
Feed voltage*	230/240 V ± 10%	
Frequency	50/60 Hz	
Maximum power	350 W	
Fuse	T 2.5A L250V	

*On the 115V version the T 5A L250V fuse must be used

SPARE PARTS CODES

GFC CODE	DESCRIPTION
P907	Complete air conveyor with grid
M1201	Hot air concentrator
P920	Motor block (230/240 V)
P922	Motor block (115 V)
P921	Heating element block (230/240 V)
P923	Heating element block (115 V)
N2.650.00.05	Fuse (230 V)
N2.650.00.04	Fuse (115 V)
N2.310.00.27	Fata on/off knob
M2F011	Fata electronic board (230/240 V-115 V)
N2.310.00.28	Heat regulation knob (F.Plus)
M2F010	Fata Plus electronic board (230/240 V)
M2F012	Fata Plus electronic board (115 V)

